

MODEL TC3000/50-6

HIGH POWER, MULTIPLE START AND CONTINUOUS DC POWER UNIT (NSN 6130-99-152-7280)



SUPPLIED WITH UNIT

Output Cable

OPTIONAL EXTRAS

Towbar

Handlebar and Casters

Various Output Cable Lengths

Various Connectors

	163000/30-0
Max amps	5000 (Nom. short circut current) 7800 (Max. short circuit current)
Capacity	114 Amp Hrs @ 10 Hr rate
Max Start Voltage	26V DC
Continuous voltage	28.5v DC
Continuous power	50 amps
AC input	95v - 270v
Size (cm)	L89 W78 H46
Weight nom kg	145
Operating Temp	-40°C - + 50° C
Case	Zinc Coated Steel
Voltage indication	LED display
Performance monitoring	LED display
Output Cable	3m heavy duty cable with aircraft connector
Charger	50A Electronic inbuilt. Charging time less than 1 hour from 50%.
Plug Selector	
UK	240V 13A (STANDARD MAINS)
USA	110V 15A (STANDARD MAINS)
Other Countries	Please state country when ordering

TC3000/50-6

PROTECTION

Overload.



Specification may change without notice

- · Weather protected.
- · Air transportable, 'Non Hazardous'
- · Maintenance free.
- · Tough and compact.
- · No memory effect.
- · High charge retention.
- · Long shelf life.
- · Fast recharge.
- · No cycling.
- · Leak proof.
- · Cells replaceable on condition.
- Multiple, heavy duty engine starting of turbo prop, turbine, aircraft and helicopters.
- · Continuous 28V DC power supply
- · Starts Main Battle Tanks.
- · Starts Armoured Fighting Vehicles.
- · Portable start power at remote locations.

Distributor:

wm-electronics sales@wmelectronic.at

www.aero.wmelectronic.at +43(0)69912559592