

## MODEL TC400A/28TR HIGH POWERED, CONTINUOUS AND MULTI START BATTERY UNIT

## No Fuel, No Pollution, and No Noise

The TC400/28 range is designed to give silent, clean power. These 28V DC power supplies can offer both continuous power for a set time, and start power. With a built in 'flashing' light, the units will tell you when it is time to charge them. They also come with a built in voltmeter and an external charger that allows you to leave them on charge when not in use, ensuring they are always ready for operation. The TC400/28 range is designed specifically for when mains power is not readily available. They are maintenance free, with no moving parts, which make these units an extremely cost effective and environmentally friendly option.



## **OPTIONAL EXTRAS**

**Cable Horns** 

**Longer Output Cables** 

	IC400A/281K
Max Amps	10,500A (Nom. short circut current) 15,600A (Max. short circuit current)
Capacity	408 Amp Hrs
Run Time	285A for 1 hour, 165A for 2 hours, 117A for 3 hours etc
Max Voltage	30.3V DC
Size (cm)	L 200 x W 108 x H 150
Weight kg	500
Operating Temp.	-40°C - +60°C
Case	Zinc coated steel
Voltage indictication	Digital to IP65
Auxiliary Protection	Circuit breaker 40A
Output Cable	3m heavy duty cable with aircraft connector
Charger	50A Electronic 110/230V. Charging time less than 3 hours from 50% (larger chargers available)

TC4001/20TD



- · Totally weather protected.
- · Air transportable, 'Non Hazardous'
- · Maintenance free.
- · Tough and compact.
- · No memory effect.
- · High charge retention.
- · Long shelf life.
- · Fast recharge.
- · External charger for prolonged unit life.
- · No cycling.
- · Leak proof.
- · Cells replaceable on condition.
- · Multiple, heavy duty engine starting.

**Distributor:** 

wm-electronics sales@wmelectronic.at www.aero.wmelectronic.at +43(0)69912559592