

MODEL TC400A-4
HIGH CAPACITY, MULTIPLE START POWER UNIT FOR AIRCRAFT AND COMBAT VEHICLES (NSN 6130-99-837-1708)



SUPPLIED WITH UNIT

Charger

Output Cable

	TC 400A-4
Maximum	3500A (Nom. short circut current) 5200A (Max. short circuit current)
Capacity Multiple Start	76 Amp Hrs
Max Voltage	26V DC
Size (cm)	L 78 x W 35 x H 30
Weight kg	105
Operating Temp.	-40°C - +60°C
Case	Zinc coated steel
Voltage indictication	Digital to IP65
Auxiliary Protection	Circuit breaker 40A
Output Cable	3m heavy duty cable with aircraft connector
Charger	20A Electronic110/230v. Charging time less than 1 hour from 50%.

Specification may change without notice

OPTIONAL EXTRAS

Towbar

Handlebar and Casters

Various Output Cable Lengths

Various Connectors



- · Totally weather protected.
- · Air transportable, 'Non Hazardous'
- · Maintenance free.
- · Tough and compact.
- · No memory effect.
- · High charge retention.
- · Long shelf life.
- · Fast recharge.
- · External charger for prolonged unit life.
- · No cycling.
- · Leak proof.
- · Cells replaceable on condition.
- · Multiple, heavy duty engine starting of turbo prop, turbine, aircraft and helicopters.
- · Starts Main Battle Tanks.
- · Starts Armoured Fighting Vehicles.
- · Portable start power at remote locations.

Distributor:

wm-electronics sales@wmelectronic.at www.aero.wmelectronic.at +43(0)69912559592