

MODEL TC400A-6

HIGH CAPACITY, MULTIPLE START POWER UNIT FOR AIRCRAFT AND COMBAT VEHICLES (NSN 2995-99-935-6323)



SUPPLIED WITH UNIT

Charger

Output Cable

TC400A-6

Maximum 5000A (Nom. short circut current) 7800A (Max. short circuit current)

Capacity Multiple 114 Amp Hrs

Start

Max Voltage 26V DC

L 78 x W 35 x H 30 Size (cm)

Weight kg 135

Output Cable

Operating Temp. -40°C - +60°C

Zinc coated steel Case **Voltage indictication** Digital to IP65

Auxiliary Protection

Circuit breaker 40A

3m heavy duty cable with aircraft connector

Charger 20A Electronic110/230v. Charging

Specification may change without notice

time less than 2 hours from 50%.

OPTIONAL EXTRAS

Towbar

Handlebar and Casters

Various Output Cable Lengths

Various Connectors

· Totally weather protected.

- · Air transportable, 'Non Hazardous'
- · Maintenance free.
- · Tough and compact.
- · No memory effect.
- · High charge retention.
- · Long shelf life.
- · Fast recharge.
- · External charger for prolonged unit life.
- · No cycling.
- · Leak proof.
- · Cells replaceable on condition.
- · Multiple, heavy duty engine starting of turbo prop, turbine, aircraft and helicopters.
- · Starts Main Battle Tanks.
- · Starts Armoured Fighting Vehicles.
- · Portable start power at remote locations.

