

MODEL TC400A-8

HIGH CAPACITY, MULTIPLE START POWER UNIT FOR AIRCRAFT AND COMBAT VEHICLES (NSN 2995-99-578-3998)



SUPPLIED WITH UNIT

Charger

Output Cable

TC400A-8

7000A (Nom. short circut current) Maximum

Capacity Multiple

Start

Max Voltage

Size (cm)

Weight kg

Operating Temp. Case

Voltage indictication

Auxiliary Protection

Output Cable

Charger

10400A (Max. short circuit current)

152 Amp Hrs

26V DC

L 78 x W 35 x H 30

165

-40°C - +60°C

Zinc coated steel

Digital to IP65

Circuit breaker 40A

3m heavy duty cable with aircraft

connector

20A Electronic110/230v. Charging

time less than 2 hours from 50%.

Specification may change without notice

OPTIONAL EXTRAS

Towbar

Handlebar and Casters

Various Output Cable Lengths

Various Connectors

- · Totally weather protected.
- · Air transportable, 'Non Hazardous'
- · Maintenance free.
- · Tough and compact.
- · No memory effect.
- · High charge retention.
- · Long shelf life.
- · Fast recharge.
- · External charger for prolonged unit life.
- · No cycling.
- · Leak proof.
- · Cells replaceable on condition.
- · Multiple, heavy duty engine starting of turbo prop, turbine, aircraft and helicopters.
- · Starts Main Battle Tanks.
- · Starts Armoured Fighting Vehicles.
- · Portable start power at remote locations.

