



REDBOX
INTERNATIONAL

TWIN RB 75A

MODEL TWIN RB 75A

HAND / AIR PORTABLE POWER UNIT FOR AIRCRAFT AND COMBAT VEHICLES



TWINRB75A

Max amps	3500 (Nom. short circuit current) 5200 (Max. short circuit current)
Capacity	76 Amp Hrs @ 10 hr rate
Max Voltage	26V DC
Size (cm)	2 X L 45 x W 10 x H 38
Weight kg	70
Operating Temp.	-40°C - +60°C
Case	Stainless steel
Voltage indication	Digital to IP65
Auxiliary Protection	Circuit breaker 40A
Output Cable	2m heavy duty cable with aircraft connector
Charger	2 X 8 A Electronic universal AC input. Charging time less than 2 hours from 50%
Protection	Reverse polarity warning

SUPPLIED WITH UNIT

2 x Charger
Output Cable
Parallel Joining Cable
Twin Trolley
2 x Thermal Protection Bag

OPTIONAL EXTRAS

Various output cable lengths
Croc Clips
Various Connectors
25A, 50A, 75A or 100A 28V DC power supply

- *Totally weather protected.*
- *Air transportable, 'Non Hazardous'*
- *Maintenance free.*
- *Tough and compact.*
- *No memory effect.*
- *Works in any orientation.*
- *High charge retention.*
- *Long shelf life.*
- *Fast recharge.*
- *External charger for prolonged unit life.*
- *No cycling.*
- *Leak proof.*
- *Cells replaceable on condition.*
- *Heavy duty engine starting of turbo prop, turbine, aircraft and helicopters.*
- *Starts Main Battle Tanks.*
- *Starts Armoured Fighting Vehicles.*
- *Lightweight portable start power at remote locations.*



www.aero.wmelectronic.at sales@wmelectronic.at

Tel +43 (0) 69912559592