

MODEL TWIN RB 85A 28V

28V STARTING SYSTEM

HAND / AIR PORTABLE POWER UNIT FOR AIRCRAFT AND COMBAT VEHICLES



| SUPPLIED WITH UNIT | |
|----------------------------|--|
| 2 x Charger | |
| Output Cable | |
| Parallel Joining Cable | |
| Twin Trolley | |
| 2 x Thermal Protection Bag | |

OPTIONAL EXTRAS Various output cable lengths Croc Clips Various Connectors 25A, 50A, 75A or 100A 28V DC power supply

| | TWI RB 85A 28V |
|-----------------------|---|
| Max amps | 3500 (Nom. short circut current) 5200 (Max. short circuit current) |
| Capacity | 76 Amp Hrs @ 10 hr rate |
| Max Voltage | 30V DC |
| Size (cm) | 2 X L 55 x W 10 x H 38 |
| Weight kg | 75 |
| Operating Temp. | -40°C - +60°C |
| Case | Stainless steel |
| Voltage indictication | Digital to IP65 |
| Auxiliary Protection | Circuit breaker 40A |
| Output Cable | 2m heavy duty cable with aircraft connector |
| Charger | 2 X 8 A Electronic universal AC input. Charging time less than 2 hours from 50% |
| Protection | Reverse polarity warning |

- · Totally weather protected.
- · Air transportable, 'Non Hazardous'
- · Maintenance free.
- · Tough and compact.
- · No memory effect.
- · Works in any orientation.
- · High charge retention.
- · Long shelf life.
- · Fast recharge.
- · External charger for prolonged unit life.
- · No cycling.
- · Leak proof.
- · Cells replaceable on condition.
- · Heavy duty engine starting of turbo prop, turbine, aircraft and helicopters.
- · Starts Main Battle Tanks.
- · Starts Armoured Fighting Vehicles.
- · Lightweight portable start power at remote locations.

Distributor:

wm-electronics sales@wmelectronic.at

www.aero.wmelectronic.at +43(0)69912559592